



FEATURES

- Digital broad range vibration measurement via internal accelerometer
- 64-Bit unique ID
- Up to 600 foot transmission range
- 30 second transmission interval
- Patent pending
- Battery life up to 5 years
- Very small (1.3" X 2.1" X .6") ABS enclosure
- Complies with part 15 of the FCC rules
- Water resistant coating for wet environments
- Internal loop antenna
- Low cost



DESCRIPTION

The Point Sensor Vibration sensor is a battery operated digital vibration sensor with a microprocessor controlled 418 MHz. FCC certified radio transmitter. The Point Sensor Vibration sensor has an on board time of day clock that allows it to spend most of the time in a low power quiescent state. At predetermined time intervals the clock will wake up the onboard microprocessor. Unique serial number information and digital Vibration data is combined with a CRC-16 error check and transmitted in a very short data packet that results in a transmitter on time of only 15 milliseconds. This architecture allows the Point Sensor Vibration sensor to consume very low energy resulting in a battery life of up to 5 years.

The electronics are coated with a conformal material that provides a moisture barrier against condensation. Submersion in water is not recommended. An integral pushbutton is used to activate the service switch. The Sensor is shipped with the transmitter turned off (anytime the Sensor is to be shipped the transmitter should be turned off or must be placed in a shielded container to prevent interference that might cause shipping problems). Start the Sensor by momentarily pushing the service switch (you will feel the button click). When the service switch is pushed a data transmission occurs immediately and a special mark is introduced in the ID field of the transmitted data packet to indicate which sensor is in service or installation. The service switch is also used to put the Sensor in a quiescent mode (no transmissions and very low power consumption). This is the state the Sensor is in when you receive it from the manufacturer. Push and hold the service switch for 5 seconds or more to enter this powered down state.

Transmission rate	30 seconds
Shelf life with battery installed	10 Years in quiescent mode
Dimensions (enclosure)	1.5 W X 2.1 H X .6 D (inches)
Weight	1.0 oz.
Storage Temperature	-40° to 85° C
Operating Temperature	-40° to 85° C
Battery life with transmissions	3-7 years
Battery	3.6 volt Lithium